

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : Foam-Lok FL 2000
 Product code : FL 2000 - All Grades
 Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
 Use of the substance/mixture : Closed-cell spray applied foam when installed following application guidelines adheres to framing members and substrates.
 Use of the substance/mixture : A component for the production of spray insulation foam

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Lapolla Industries, Inc.
 15402 Vantage Parkway East, Ste. 322
 Houston, Texas 77032
 Tel: +1 281 219 4100, (877) 636-2648
 Email: sds@lapolla.com

1.4. Emergency telephone number

Emergency number : CARECHEM (866) 928-0789

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation Category 2 H315
 Serious eye damage/eye irritation, Category 1 H318
 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

To avoid risks to human health and the environment, comply with the instructions for use.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (CLP) :

P264 - Wash hands, face thoroughly after handling
 P273 - Avoid release to the environment
 P280 - Wear eye protection, protective clothing, protective gloves
 P302+P352 - IF ON SKIN: Wash with plenty of water
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a doctor, a POISON CENTER

2.3. Other hazards

No additional information available

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Propanol, 1-chloro-, phosphate (3:1)	(CAS No) 13674-84-5 (EC no) 237-158-7	<20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332
Oxirane, methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-nonylphenol (5:1)	(CAS No) 52019-35-9 (EC no) 610-766-3	<15	Eye Dam. 1, H318
Diethylene glycol	(CAS No) 111-46-6 (EC no) 203-872-2 (EC index no) 603-140-00-6	<10	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
1-Propanol, 2,2-dimethyl-, tribromo derivative	(CAS No) 36483-57-5 (EC no) 253-057-0	<10	Acute Tox. 4 (Oral), H302
1,3-Propanediamine, N,N-bis[3-(dimethylamino)propyl]-N',N'-dimethyl-	(CAS No) 33329-35-0 (EC no) 251-459-0	0,5 - 3	Acute Tox. 4 (Dermal), H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Ethylene glycol	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1	0.1 - 0.75	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Bis(2-dimethylaminoethyl) ether	(CAS No) 3033-62-3 (EC no) 221-220-5	<0.5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of breathing difficulties administer oxygen. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical advice.
First-aid measures after skin contact	: Remove contaminated clothing immediately. Wash skin thoroughly with mild soap and water. Seek medical attention immediately.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Contact lenses should be removed. Immediately get medical attention.
First-aid measures after ingestion	: Rinse mouth immediately and drink plenty of water. Call a POISON CENTER or doctor/physician. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in the recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Inhalation of mist or aerosol may cause irritation to nose and throat . May cause irritation to the respiratory tract.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Can occur: Gastrointestinal disturbance. Tremor. Cardiac disorders. Incoordination, dizziness, headache, nausea, mental confusion slurred speech depending to quantity of ingested material.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water. Dry extinguishing powder. Carbon dioxide. Foam.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protective equipment for firefighters	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: Prevent entry to sewers and public waters.

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Spills of this product present a serious slipping hazard. Avoid breathing mist or vapour. Avoid contact with skin, eyes and clothing.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing. Refer to section 8.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ensure adequate ventilation.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into inert absorbent material. Sweep or shovel spills into appropriate container for disposal. Ensure all national/local regulations are observed.

6.4. Reference to other sections

Refer to sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid mixing with air or use for any purpose above atmospheric pressure. Product should not be mixed with air above atmospheric pressure for leak testing or any other purpose. Use dry nitrogen to transfer or leak test equipment pressurized with product.

Hygiene measures : Wash contaminated clothing prior to re-use. Always wash hands and face immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

Storage conditions : Keep out of direct sunlight. Store in original container. Keep container tightly closed in a cool, well-ventilated place. Keep away from heat. Do not freeze. Product that is frozen and/or tending to sedimentation can be liquefied or homogenized by careful application of indirect heat (do not use flames or direct contact with a heat source). Protect from moisture.

Storage temperature : 21 - 26 °C (70 - 80 °F)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol (107-21-1)		
EU	Local name	Ethylene glycol
EU	IOELV TWA (mg/m ³)	52 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	104 mg/m ³
EU	IOELV STEL (ppm)	40 ppm
EU	Notes	Skin
Austria	MAK (mg/m ³)	26 mg/m ³
Austria	MAK (ppm)	10 ppm
Austria	MAK Short time value (mg/m ³)	52 mg/m ³
Austria	MAK Short time value (ppm)	20 ppm
Bulgaria	OEL TWA (mg/m ³)	52 mg/m ³
Bulgaria	OEL TWA (ppm)	20 ppm
Bulgaria	OEL STEL (mg/m ³)	104 mg/m ³
Bulgaria	OEL STEL (ppm)	40 ppm
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	52 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	20 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	104 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	40 ppm

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylene glycol (107-21-1)		
Cyprus	OEL TWA (mg/m ³)	52 mg/m ³
Cyprus	OEL TWA (ppm)	20 ppm
Cyprus	OEL STEL (mg/m ³)	104 mg/m ³
Cyprus	OEL STEL (ppm)	40 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	50 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	26 mg/m ³ 10 mg/m ³ (vapor)
Denmark	Grænseværdie (langvarig) (ppm)	10 ppm
Estonia	OEL TWA (mg/m ³)	52 mg/m ³ (total concentration of aerosol and vapor)
Estonia	OEL TWA (ppm)	20 ppm (total concentration of aerosol and vapor)
Estonia	OEL STEL (mg/m ³)	104 mg/m ³ (total concentration of aerosol and vapor)
Estonia	OEL STEL (ppm)	40 ppm (total concentration of aerosol and vapor)
Finland	HTP-arvo (8h) (mg/m ³)	50 mg/m ³
Finland	HTP-arvo (8h) (ppm)	20 ppm
Finland	HTP-arvo (15 min)	100 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	40 ppm
France	Local name	Ethylèneglycol (vapeur)
France	VME (mg/m ³)	52 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	104 mg/m ³
France	VLE (ppm)	40 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	26 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	10 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Gibraltar	OEL TWA (mg/m ³)	52 mg/m ³
Gibraltar	OEL TWA (ppm)	20 ppm
Gibraltar	OEL STEL (mg/m ³)	104 mg/m ³
Gibraltar	OEL STEL (ppm)	40 ppm
Greece	OEL TWA (mg/m ³)	125 mg/m ³ (vapor)
Greece	OEL TWA (ppm)	50 ppm (vapor)
Greece	OEL STEL (mg/m ³)	125 mg/m ³ (vapor)
Greece	OEL STEL (ppm)	50 ppm (vapor)
Hungary	AK-érték	52 mg/m ³
Hungary	CK-érték	104 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	10 mg/m ³ (particulate) 52 mg/m ³ (vapour)
Ireland	OEL (8 hours ref) (ppm)	20 ppm (vapour)
Ireland	OEL (15 min ref) (mg/m ³)	104 mg/m ³ (vapour)
Ireland	OEL (15 min ref) (ppm)	40 ppm (particulate)
Italy	OEL TWA (mg/m ³)	52 mg/m ³
Italy	OEL TWA (ppm)	20 ppm
Italy	OEL STEL (mg/m ³)	104 mg/m ³
Italy	OEL STEL (ppm)	40 ppm
Latvia	OEL TWA (mg/m ³)	52 mg/m ³
Latvia	OEL TWA (ppm)	20 ppm
Lithuania	IPRV (mg/m ³)	25 mg/m ³ (aerosol and vapor)
Lithuania	IPRV (ppm)	10 ppm (aerosol and vapor)
Lithuania	TPRV (mg/m ³)	50 mg/m ³ (aerosol and vapor)
Lithuania	TPRV (ppm)	20 ppm (aerosol and vapor)
Luxembourg	OEL TWA (mg/m ³)	52 mg/m ³

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylene glycol (107-21-1)		
Luxembourg	OEL TWA (ppm)	20 ppm
Luxembourg	OEL STEL (mg/m ³)	104 mg/m ³
Luxembourg	OEL STEL (ppm)	40 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	52 mg/m ³ (fume) 10 mg/m ³ (droplets)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	104 mg/m ³
Poland	NDS (mg/m ³)	15 mg/m ³
Poland	NDSch (mg/m ³)	50 mg/m ³
Portugal	OEL TWA (mg/m ³)	52 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	20 ppm (indicative limit value)
Portugal	OEL STEL (mg/m ³)	104 mg/m ³ (indicative limit value)
Portugal	OEL STEL (ppm)	40 ppm (indicative limit value)
Portugal	OEL - Ceilings (mg/m ³)	100 mg/m ³ (aerosol only)
Romania	OEL TWA (mg/m ³)	52 mg/m ³
Romania	OEL TWA (ppm)	20 ppm
Romania	OEL STEL (mg/m ³)	104 mg/m ³
Romania	OEL STEL (ppm)	40 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	52 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	20 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	104 mg/m ³
Slovenia	OEL TWA (mg/m ³)	52 mg/m ³
Slovenia	OEL TWA (ppm)	20 ppm
Slovenia	OEL STEL (mg/m ³)	104 mg/m ³
Slovenia	OEL STEL (ppm)	40 ppm
Spain	VLA-ED (mg/m ³)	52 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	20 ppm (indicative limit value)
Spain	VLA-EC (mg/m ³)	104 mg/m ³
Spain	VLA-EC (ppm)	40 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	25 mg/m ³ (aerosol and vapor)
Sweden	nivågränsvärde (NVG) (ppm)	10 ppm (aerosol and vapor)
Sweden	kortidsvärde (KTV) (mg/m ³)	50 mg/m ³ (aerosol and vapor)
Sweden	kortidsvärde (KTV) (ppm)	20 ppm (aerosol and vapor)
United Kingdom	Local name	Ethane-1,2-diol
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ particulate 52 mg/m ³ vapour
United Kingdom	WEL TWA (ppm)	20 ppm vapour
United Kingdom	WEL STEL (mg/m ³)	104 mg/m ³ vapour
United Kingdom	WEL STEL (ppm)	40 ppm vapour
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Diethylene glycol (111-46-6)		
Austria	MAK (mg/m ³)	44 mg/m ³
Austria	MAK (ppm)	10 ppm
Austria	MAK Short time value (mg/m ³)	176 mg/m ³
Austria	MAK Short time value (ppm)	40 ppm
Bulgaria	OEL TWA (mg/m ³)	10 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	101 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	23 ppm
Denmark	Grænseværdie (langvarig) (mg/m ³)	11 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	2,5 ppm
Estonia	OEL TWA (mg/m ³)	45 mg/m ³
Estonia	OEL TWA (ppm)	10 ppm
Estonia	OEL STEL (mg/m ³)	90 mg/m ³

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Diethylene glycol (111-46-6)		
Estonia	OEL STEL (ppm)	20 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	44 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	10 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Ireland	OEL (8 hours ref) (mg/m ³)	100 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	23 ppm
Ireland	OEL (15 min ref) (mg/m ³)	300 mg/m ³ (calculated)
Ireland	OEL (15 min ref) (ppm)	69 ppm (calculated)
Latvia	OEL TWA (mg/m ³)	10 mg/m ³
Lithuania	IPRV (mg/m ³)	45 mg/m ³
Lithuania	IPRV (ppm)	10 ppm
Lithuania	TPRV (mg/m ³)	90 mg/m ³
Lithuania	TPRV (ppm)	20 ppm
Poland	NDS (mg/m ³)	10 mg/m ³ (inhalable fraction)
Romania	OEL TWA (mg/m ³)	500 mg/m ³
Romania	OEL TWA (ppm)	115 ppm
Romania	OEL STEL (mg/m ³)	800 mg/m ³
Romania	OEL STEL (ppm)	184 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	44 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	10 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	90 mg/m ³
Slovenia	OEL TWA (mg/m ³)	44 mg/m ³
Slovenia	OEL TWA (ppm)	10 ppm
Slovenia	OEL STEL (mg/m ³)	176 mg/m ³
Slovenia	OEL STEL (ppm)	40 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	45 mg/m ³ (the limit value applies to the combined concentration of vapour and aerosol)
Sweden	nivågränsvärde (NVG) (ppm)	10 ppm (the limit value applies to the combined concentration of vapour and aerosol)
Sweden	kortidsvärde (KTV) (mg/m ³)	90 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	20 ppm
United Kingdom	Local name	2,2'-Oxydiethanol
United Kingdom	WEL TWA (mg/m ³)	101 mg/m ³
United Kingdom	WEL TWA (ppm)	23 ppm
United Kingdom	WEL STEL (mg/m ³)	303 mg/m ³ (calculated)
United Kingdom	WEL STEL (ppm)	69 ppm (calculated)
Triethylene glycol (112-27-6)		
Bulgaria	OEL TWA (mg/m ³)	15,0 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1000 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-inhalable fraction)
Romania	OEL TWA (mg/m ³)	700 mg/m ³
Romania	OEL TWA (ppm)	114 ppm
Romania	OEL STEL (mg/m ³)	1000 mg/m ³
Romania	OEL STEL (ppm)	163 ppm
Bis(2-dimethylaminoethyl) ether (3033-62-3)		
Belgium	Limit value (mg/m ³)	0,33 mg/m ³
Belgium	Limit value (ppm)	0,05 ppm
Belgium	Short time value (mg/m ³)	1 mg/m ³
Belgium	Short time value (ppm)	0,15 ppm
Portugal	OEL TWA (ppm)	0,05 ppm

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Bis(2-dimethylaminoethyl) ether (3033-62-3)

Portugal

OEL STEL (ppm)

0,15 ppm

8.2. Exposure controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation. Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Personal protective equipment	: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.
Hand protection	: Wear suitable gloves resistant to chemical penetration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. (to European standard EN 374 or equivalent)
Eye protection	: Tightly fitting safety goggles. Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles. Chemical goggles should be consistent with EN166 or equivalent.
Skin and body protection	: Protective clothing
Respiratory protection	: Full face piece respirator. Approved supplied air respirator



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Dark orange brown.
Odour	: Amine-like.
Odour threshold	: No data available
pH	: ≥ 7
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C (closed cup)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,15 - 1,17 g/cm ³ @ 25°C (Bulk Density)
Solubility	: Water: Slightly soluble
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 800 - 1000 mPa.s @ 23 °C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in use and storage conditions as recommended in item 7.

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Temperatures > 26 °C. Moisture. Direct sunlight. Heat.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on additivity formula, the classification criteria are not met)

Additional information : May cause gastrointestinal irritation, nausea, vomiting and diarrhea

Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg
Diethylene glycol (111-46-6)	
LD50 oral rat	12565 mg/kg
LD50 dermal rabbit	11890 mg/kg
2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)	
LD50 oral rat	930 - 1550 mg/kg
LD50 dermal rabbit	1230 mg/kg
LC50 inhalation rat (mg/l)	5 mg/l/4h
1-Propanol, 2,2-dimethyl-, tribromo derivative (36483-57-5)	
LD50 oral rat	1630 mg/kg
Bis(2-dimethylaminoethyl) ether (3033-62-3)	
LD50 oral rat	910 mg/kg
LD50 dermal rabbit	238 mg/kg
LC50 inhalation rat (ppm)	117 ppm (Exposure time: 6 h)

Skin corrosion/irritation : Causes skin irritation.
pH: >= 7

Serious eye damage/irritation : Causes serious eye damage.
pH: >= 7

Respiratory or skin sensitisation : Not classified (none of the components are classified for respiratory or skin sensitization)

Germ cell mutagenicity : Not classified (No classification for mutagenicity as none of the components are classified for mutagenicity)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (No classification for reproduction as none of the components are toxic for reproduction)

Specific target organ toxicity (single exposure) : Not classified (Based on available data, the classification criteria are not met)

Specific target organ toxicity (repeated exposure) : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

Ethylene glycol (107-21-1)	
LC50 fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h algae (1)	6500 - 13000 mg/l (Species: Pseudokirchneriella subcapitata)
Diethylene glycol (111-46-6)	
LC50 fish 1	75200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	84000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)	
LC50 fish 2	180 mg/l (Exposure time: 96 h - Species: Leuciscus idus [static])

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)	
EC50 other aquatic organisms 2	4 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
EC50 72h algae (1)	45 mg/l (Species: Desmodesmus subspicatus)
EC50 96h algae (1)	4 mg/l (Species: Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethylene glycol (107-21-1)	
Log Pow	-1,93

Diethylene glycol (111-46-6)	
BCF fish 1	100 - 180
Log Pow	-1,98 (at 25 °C)

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)	
BCF fish 1	1,9 - 4,6
Log Pow	2,59

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Foam-Lok FL 2000	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Consult the appropriate authorities about waste disposal. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Product wastes can often be incinerated in approved facilities. Consult the appropriate authorities about waste disposal.
Additional information	: Do not re-use empty containers. Do not dispose of waste into sewer. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Container Disposal: Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers). Decontaminate containers prior to disposal. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. Ensure all national/local regulations are observed.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not regulated
Proper Shipping Name (IMDG)	: Not regulated
Proper Shipping Name (IATA)	: Not regulated
Proper Shipping Name (ADN)	: Not regulated
Proper Shipping Name (RID)	: Not regulated

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: Not applicable
----------------------------------	------------------

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations : Compliance with following regulations: Directive 1999/45/EC as amended. Directive 67/548/EEC as amended. Regulation (EC) 1907/2006 as amended. Regulation (EC) 1272/2008 as amended.

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Foam-Lok FL 2000

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed

Denmark

Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product
-----------------------------------	---

15.2. Chemical safety assessment

CSA has not been established

SECTION 16: Other information

CAS - Chemical Abstracts Service
CSR - Chemical Safety Report
EC - European Community
EEC - European Economic Community
MSDS - Material Safety Data Sheet
PBT - Persistent, Bioaccumulative and Toxic substance
SDS - Safety Data Sheet
STEL- Short-Term Exposure Limit
TLV- Threshold Limit Value
TWA- Time Weighted Average
vPvB - Very Persistent and Very Bioaccumulative

Date of Preparation : May 3, 2016

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H332	Harmful if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

SDS EU (REACH Annex II)

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY LAPOLLA INDUSTRIES, INC. HEREUNDER ARE GIVEN GRATIS AND LAPOLLA INDUSTRIES, INC. ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. LAPOLLA INDUSTRIES, INC. WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.